

EUNICOTE AC14 Clear

Protective Coating and Waterproofing for Concrete



Product Description

EUNICOTE AC14 Clear system is a range of protective membranes based on acrylic resins. EUNICOTE AC14 forms an elastic durable matrix within cementitious substrates.

Typical Properties

Appearance: White liquid

Specific Gravity: 1.0 at 20°C

Shelf Life: 12 months in sealed containers.

Uses

EUNICOTE AC14 clear is used as a protective sealer for all types of cementitious, concrete panels, stone, cladding and other precast elements.

- Acts as a protective sealer.
- Can be applied on damp surfaces.
- EUNICOTE AC14 is a non-degrading sealer, non-yellowing, stable product.

Application

Coverage (per coat): 5 m²/lit

Touch Dry: 2-4 hours

Full Dry: 24 hours

Service

Film thickness is penetrative.

Substrate Control	10 min	30 min	60 min
(uncoated) EUNICOTE	1.170	0.770	0.460
AC14 clear	0.030	0.020	0.010

Mixing

EUNICOTE AC14 is supplied ready to use. Some settlement may occur in EUNICOTE AC14 clear which should be mixed well before use.

Cleaning

All equipment should be cleaned immediately after use with thinners or Xylene.

Packaging

EUNICOTE AC14 is available in 25 liters kit, 210 liters Drums.

Technical Service

The Technical Department is available to assist you in the correct use of our products and its resources are at your disposal entirely without obligation.

Contact Information

Al-Faiha for Engineering Products

techsupport@alfaihaengineering.com

www.alfaihaengineering.com